

# IDEAL HERBICIDE 2/3 ROW VINEYARD SPRAYER

## SPECIFICATIONS

### TANK

Impact resistant polyethylene tanks with UV-stabilised finish.  
Calibrated sight gauge, flip-open filling lid with large basket strainer.  
Quick fill system.

5000 litre main tank.

4000 litre main tank.

3000 litre main tank.

2000 litre main tank.

Separate 15 litre fresh water tank.

### PUMP

Low pressure pump – Comet BP125 (max. 20-bar) - large capacity  
(125 L/min) three diaphragm pump.

### DRIVE

Heavy duty PTO driveshaft comes with safety covers and quick  
release pins. Optional constant velocity (CV) shaft available.

### CONTROLS

Standard Electric - motor valves, 2 section in-cab control with electric  
pressure adjustment.

Optional Bravo 180 automatic rate controller, 2 section (left/right) with  
optional

4-section control. ISO Bus module available

### AGITATION

5000, 4000, 3000, 2000 litre - twin brass agitators.

Optional hypro hydraulic pump.

### FILTRATION

Full filtration system - tank filling basket, suction filter and optional  
pressure filters.

### NOZZLES

Standard fitted with one set of TDAM air mix air induced  
nozzles.

Note - You can specify your nozzle selection on your order if you  
know the calibration requirements of the sprayer for your customer.



### CHASSIS & BOOM

Powder Coated, full-length with adjustable drawbar and  
6- stud wheel hubs. Fixed axle standard; optional  
adjustable height and width axle. Jockey stand supplied on all  
models.

Two and three row booms available with hydraulic fold, lift, side shift  
on request.

Hot-dipped galvanised is available on request.

### WHEELS

5000, 4000, 3000 litre - steel rims, 400/60 x 15.5" flotation tyres  
2000 - steel rims, 12.5/80 x 15.3"

### DIMENSIONS

5000 litre - 5.5m L x 2.6m W x 2.2m H

4000 litre - 5.5m L x 2.6m W x 2.2m H

3000 litre - 5.2m L x 2.1m W x 3.1m H

2000 litre - 4.7m L x 2.1m W x 3.1m H

Note - dimensions may vary where different options are  
applied.