

IDEAL HERBICIDE SINGLE ROW ORCHARD / VINEYARD SPRAYER

SPECIFICATIONS

TANK

Impact resistant polyethylene tanks with UV-stabilised finish. Calibrated sight gauge, flip-open filling lid with large basket strainer. Quick fill system.

5000 litre main tank.

4000 litre main tank.

3000 litre main tank.

2000 litre main tank.

Separate 15 litre fresh water tank.

PUMP

Low pressure pump – Comet BP125 (max. 20-bar) - large capacity (125 L/min) three diaphragm pump.

DRIVE

Heavy duty PTO driveshaft comes with safety covers and quick release pins. Optional constant velocity (CV) shaft available.

CONTROLS

Standard Electric - motor valves, 3 section in-cab control with electric pressure adjustment.

Optional Bravo 180 automatic rate controller, 3 section (left/right) with optional

ISO Bus module available.

AGITATION

5000, 4000, 3000, 2000 litre - twin brass agitators.

Optional hypro hydraulic pump.

FILTRATION

Full filtration system - tank filling basket, suction filter and optional pressure filters.

NOZZLES

Standard fitted with one set of TDAM air mix air inducted nozzles.

Note - You can specify your nozzle selection on your order if you know the calibration requirements of the sprayer for your customer.



CHASSIS & BOOM

Powder Coated, full-length with adjustable drawbar and 6- stud wheel hubs. Fixed axle standard; optional adjustable height and width axle. Jockey stand supplied on all models.

Booms available with hydraulic fold, lift, side shift on request.

Hot-dipped galvanised is available on request.

WHEELS

5000, 4000, 3000 litre - steel rims, 400/60 x 15.5" flotation tyres
2000 - steel rims, 12.5/80 x 15.3"

DIMENSIONS

5000 litre - 5.5m L x 2.6m W x 1.6m H

4000 litre - 5.5m L x 2.6m W x 1.6m H

3000 litre - 5.2m L x 2.1m W x 1.6m H

2000 litre - 4.7m L x 2.1m W x 1.6m H