

Agromaxx SERIES



DEUTZ-FAHR
Agromaxx 60 HD



DEUTZ-FAHR Agromaxx 60 HD

DEALER:

TECHNICAL DATA

AGROMAXX 60 HD

| ENGINE | | 1000.3 W |
|----------------------------|---------------------|--------------------------------------|
| Cylinders/Displacement | no./cm ³ | 3 / 3000 |
| Aspiration | | Natural |
| Max. homologated net power | HP/kW | 60 / 44 |
| Nominal engine speed | rpm | 2350 |
| Max. torque | Nm | 234 |
| Cooling | | liquid-oil |
| Engine control | | mechanical |
| Air cleaner | | dry type air filter with pre-cleaner |
| Silencer underhood | | with vertical exhaust pipe |
| Fuel tank capacity | litres | 56 |

| DIMENSIONS AND WEIGHTS (with rear tyres) | | 14.9 x 28 |
|--|----|-----------|
| Max. length without link arms | mm | 3225 |
| Min - max. width | mm | 1822/2336 |
| Max. height at engine hood | mm | 1355 |
| Max. height at steering wheel | mm | 1505 |
| Ground clearance | mm | 335 |
| Wheelbase | mm | 2045 |
| Front track - max. | mm | 1740 |
| Rear track - max. | mm | 1800 |
| Minimum steering radius without braking | mm | 3700 |
| Weight with safety frame | kg | 2300 |

| TRANSMISSION | |
|--|---|
| Gearbox clutch | mechanically operated |
| Mechanical gearbox, 4 synchronised gears, 3 gear range | 12 FWD + 3 REV |
| Max. speed | km/h 30 |
| Shuttle | reverse shuttle mechanical |
| Rear differential lock | mechanically operated |
| Lubrication | forced |
| BRAKES AND STEERING | |
| Braking system | discs in oil bath on rear tyres, hydrostatically operated |
| Parking brake | independent |
| Steering | mechanical |
| | hydrostatic |
| Steering angle | 4WD 55° |

| FRONT AXLE | |
|--|-------------------------|
| Drive engagement | mechanically operated |
| Front differential lock | mechanically operated |
| REAR P.T.O. | |
| Clutch | dry type |
| Speed | rpm 540 |
| Operation | mechanical, independent |
| HYDRAULIC LIFT | |
| Rear power lift | mechanical |
| Maximum lifting capacity | kg 1500 |
| Pump delivery | l/min. 33 |
| Auxiliary hydraulic control valves | ways 2/4 |
| 3 point linkage (link arms and top link) | fixed hitching balls |
| RH link arm and stabilisers | mechanical |
| DRIVING POSITION | |
| Gears levers | lateral |
| Protection | 2 post fixed rops |
| Instruments | analog |
| Driver's seat | mechanical adjustment |

| 12 FWD + 3 REV - SPEED IN KPM AT AN ENGINE SPEED OF 2350 RPM WITH 14.9 X 28 REAR TYRES | | | | | | | | | | | |
|--|------|------|------|------|------|------|-------|------|-------|-------|-------|
| 1L | 2L | 3L | 4L | 1M | 2M | 3M | 4M | 1V | 2V | 3V | 4V |
| 0,81 | 1,25 | 2,07 | 2,91 | 2,86 | 4,38 | 7,27 | 10,21 | 9,21 | 14,12 | 23,44 | 32,94 |

For exact specifications please consult your local Deutz-Fahr dealer. The above specifications refer to tractors with all available equipment. For standard equipment and options, refer to the current price list and ask your local dealer for details.