



AUTOMOTIVE
PRODUCTS



First choice for oils



HI-TEC OILS FIRST CHOICE FOR OILS

Hi-Tec Oils is an Australian owned company with more than 200 years of total workforce experience in lubricants. We are one of Australia's largest independent oil manufacturers, with warehouses in every state and territory of Australia, and have now launched into the New Zealand market!

Our state of the art blending plant produces a range of high quality oil products based on our ongoing partnership with leading international base oil and additive suppliers. We only use product's that meet or exceed the relevant API and SAE standards.

The product range includes oils for a wide range of automotive, industrial, agricultural, transport and heavy equipment applications (diesel and petrol engine oils, gear oils, automatic transmission oils, coolants and brake fluids and specialty products).

Our lubricant range of over 450 line items consists of full synthetic, semi-synthetic and mineral oils, greases, specialty products, solvent degreaser, hand cleaner, emergency spill kits and dispensing equipment such as grease guns and oil pumps.

Head Office Site Area: 2.5 acres

Distribution Offices: Sydney (Head Office), Melbourne, Brisbane, Adelaide, Perth, Darwin, Tasmania, Canberra, Newcastle, Port Lincoln, Auckland NZ, Christchurch NZ

Base Oil Stocks: In excess of 950,000Lt









Base Oil Stocks: Mineral, Semi-Synthetic, Full Synthetic, Group I Mineral, Group II Mineral, Group III Synthetic, Ester Synthetic, PAO Synthetic

Buildings: Head Office Dispatch: 3,500sqm

Blending Vessels: 7

Although every care is taken to ensure accuracy and completeness in compiling this data, no liability can be accepted by Hi-Tec Oils for damage or loss caused by any errors or omissions in the information given, directly or indirectly. Suitability of products referred to in this catalogue is the customers sole responsibility. Always refer to technical data to confirm suitability which is available on request from Hi-Tec Oils.

CONTENTS

	EVOLUTION OILS	2
	PETROL AND LIGHT DIESEL ENGINE OILS	3-8
	DIESEL ENGINE OILS	9-10
	AUTOMATIC TRANSMISSION OILS	11-12
	AUTOMOTIVE GEAR OILS	13-14
	COOLANT & BRAKE FLUIDS	15-16
	SPECIALTY PRODUCTS	17-21
	GREASES	22-23
	HI-TEC PUMPING EQUIPMENT	24





EVOLUTION 10W/40 SN/CF A3/B4

Hi-Tec Evolution 10W/40 Semisyn SN/CF A3/B4 is a premium quality API SN/CF engine oil boosted with full synthetic Group III base oils to provide increased engine protection through increased oxidation resistance. It is suitable for most types of petrol, diesel, and LPG four stroke engines under both severe and varied operating conditions. It is ideal for use in the professional workshop.

SPECIFICATIONS

Product Code	H11-2101
API	SN, SM, SL, SJ, SH, CF, CD
ACEA	A3/B3-08; A3/B4-08
Performance	Mercedes Benz: MB 229.1; RN 0700
Product Sizes	5L, 20L, 200L and Bulk



EVOLUTION 5W/30 SN GF-5

Hi-Tec Evolution 5W/30 SN/GF-5 is the ultimate lubricant for engine protection and fuel efficiency in new as well as older petrol and small diesel engines. It meets the API SN and ILSAC GF-5 Energy Conserving III requirements.

SPECIFICATIONS

Product Code	H11-2117
API	SN, SM, SL, SJ, SH Energy Conserving III, II
ILSAC	GF-5, GF-4, GF-3
Product Sizes	5L, 20L, 200L and Bulk



EVOLUTION 15W/40 SN/CF A3/B4

Hi-Tec Evolution 15W/40 SN/CF A3/B4 is a premium quality API SN/CF engine oil boosted with full synthetic Group III base oils to provide increased engine protection through increased oxidation resistance. It is suitable for most types of petrol, diesel, and LPG four stroke engines under both severe and varied operating conditions. It is ideal for use in the professional workshop.

SPECIFICATIONS

Product Code	H11-2100
API	SN, SM, SL, SJ, SH, CF, CE, CD
ACEA	A3/B3-08, A3/B4-08
Performance	Mercedes Benz MB 229.1; RN 0700
Product Sizes	5L, 20L, 200L and Bulk



EVOLUTION 10W/30 SN GF-5

Hi-Tec Evolution 10W/30 SN/GF-5 is the ultimate lubricant for engine protection and fuel efficiency in new as well as older petrol and small diesel engines. It meets the API SN and ILSAC GF-5 Energy Conserving III requirements.

SPECIFICATIONS

Product Code	H11-2115
API	SN, SM, SL, SJ, SH Energy Conserving III, II
ILSAC	GF-5, GF-4, GF-3
Product Sizes	5L, 20L, 200L and Bulk



SYNPLUS™ 5W/30 SN/CF

Hi-Tec Synplus™ 5W/30 SN/CF is a full synthetic, low SAPS next generation oil designed for the latest super high performance, multivalve, overhead cam, turbo and light diesel engines requiring a low viscosity lubricant for better fuel economy. It is especially suited for vehicles fitted with DPF and catalytic converters to assist in lower exhaust emissions.

SPECIFICATIONS

Product Code	HII-2076
API	SN, SM, SL, SJ, SH, CF, CE, CD
ACEA	A3/B3-08, A3/B4-08, C3-12
Performance	MB 229.31, 229.51; BMW Longlife LL-04; General Motors: dexos 2™
Product Sizes	1L, 5L, 10L, 20L, 200L, 1000L and Bulk



SYNPLUS™ 5W/40 SN/CF

Hi-Tec Synplus™ 5W/40 SN/CF is a full synthetic, low SAPS next generation oil designed for the latest super high performance, multivalve, overhead cam, turbo and light diesel engines requiring a low viscosity lubricant for better fuel economy for your vehicle. It is especially suited for vehicles fitted with DPF and catalytic converters to assist in lower exhaust emissions.

SPECIFICATIONS

Product Code	HII-2077
API	SN, SM, SL, SJ, SH, CF, CE, CD
ACEA	A3/B3-08, A3/B4-08, C3-12
Performance	MB 229.31, 229.51; BMW Longlife LL-04; Porsche; General Motors: dexos 2™; Renault RN0700, 0710
Product Sizes	1L, 5L, 20L, 200L, 1000L and Bulk



SYNPLUS™ 5W/30 504/507

Hi-Tec Synplus™ 5W/30 504/507 is a full synthetic high performance engine oil designed for the latest Volkswagen petrol and turbo diesel engines, which combines the latest development in oil formulation and additive technology to provide an engine oil with the highest level of protection.

SPECIFICATIONS

Product Code	HII-2097
API	SN, SM
ACEA	C3-12
Performance	Volkswagen VW 504.00; Volkswagen VW 507.00; MB 229.51, BMW Longlife LL-04; Porsche C30
Product Sizes	5L, 20L, 200L, 1000L and Bulk



SYNPLUS™ 5W/30 DXS

Hi-Tec Synplus™ 5W/30 DXS is a full synthetic, high performance petrol engine oil designed to meet the General Motors dexos 1™ performance standard. It combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection whilst promoting fuel efficiency in modern low friction engines.

SPECIFICATIONS

Product Code	HII-2105
API	SN, SN-RC, SM, SL, SJ, SH
ILSAC	GF-5, GF-4
Performance	General Motors: dexos 1™; GM-LL-A-025, GM 4718M, GM 6094M
Product Sizes	5L, 20L, 200L, 1000L and Bulk



SYNPLUS™ 5W/30 DL-1

Hi-Tec Synplus™ 5W/30, DL-1 ACEA C1, C2 is a full synthetic, low to mid SAPS, super high performance engine oil which combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection whilst promoting fuel efficiency in modern low friction diesel engines.

SPECIFICATIONS

Product Code	HII-2106
ACEA	C1/C2-10
JASO	DL-1
Performance	Ford: WSS-M2C-934B
Product Sizes	5L, 10L, 20L, 200L, 1000L and Bulk



SYNPLUS™ 5W/30 A5/B5

Hi-Tec Synplus™ 5W/30 A5/B5 SN/CF is a full synthetic, low SAPS next generation oil designed for the latest super high performance, multivalve, overhead cam, turbo and light diesel engines requiring a low viscosity lubricant for better fuel economy. It is especially suited for vehicles fitted with DPF and catalytic converters to assist in lower exhaust emissions.

SPECIFICATIONS

Product Code	HII-2103 (0W/30); HII-2112 (5W/30)
API	SL, CF (5W/30); SL, SJ, SH, CF, CE, CD (0W/30)
ACEA	A5/B5-12, A1/B1-12 (5W/30); A5/B5-08 (0W/30)
Performance	Ford: WSS-M2C-913D, WSS-M2C-913C, WSS-M2C-913B, WSS-M2C-913
Product Sizes	5L, 20L, 200L, 1000L and Bulk



SYNPLUS™ 0W/20 & 5W/20 SN GF-5

Hi-Tec Synplus™ 0W/20 & 5W/20 SN GF-5 are the ultimate full synthetic lubricants for engine protection and fuel efficiency. They exceed the latest API SN specification, have ILSAC GF-5 fuel efficiency performance, are suitable for older API petrol specifications, and have been particularly developed for vehicles requiring the thinner API 0W/20 viscosity grade (such as some later model Subaru vehicles).

SPECIFICATIONS

Product Code	HII-2114 (0W/20); HII-2110 (5W/20)
API	SN, SM, SL; API Resource Conserving
ILSAC	GF-5, GF-4, GF-3
5W/20 Performance	Chrysler MS6395; Ford WSS-M2C-945A, Ford WSS-M2C-930A
Product Sizes	5L, 20L, 200L and Bulk



SYNPLUS™ 5W/30 ACEA C4

Hi-Tec Synplus™ 5W/30 ACEA C4 is a full synthetic, low to mid SAPS, high performance engine oil which combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection whilst promoting fuel efficiency in modern low friction diesel engines.

SPECIFICATIONS

Product Code	HII-2107
ACEA	C4-10
Performance	Renault RN 0720
Product Sizes	5L, 20L and 200L



SYNPLUS™ 5W/30 & 5W/40 LL-01

Hi-Tec Synplus™ 5W/30 & 5W/40 LL-01 are full synthetic, mid SAPS, super high performance engine oils which combine the latest development in oil formulation and additive technology to provide lubricating oil with the highest level of protection.

SPECIFICATIONS

Product Code	HII-2108 (5W/30); HII-2109 (5W/40)
API	SN, SM, SL, CF (5W/40); SL, CF (5W/30)
ACEA	A3/B3-12, A3/B4-12
Performance	BMW Longlife LL-01; MB 229.5, 229.3, 226.5; VW 502.00, 505.00; Opel/GM LL-B-025; Renault RN 0700, RN 0710; PSA B712296 (5W/40 only)
Product Sizes	5L, 20L, 200L, 1000L and Bulk



SYNPLUS™ 10W/50 SN

Hi-Tec Synplus™ 10W/50 SN is a full synthetic, low SAPS, super high performance engine oil which combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection.

SPECIFICATIONS

Product Code	HII-2098
API	SN, SM, SL, SJ, SH, CF, CE, CD
ACEA	A3/B3-08, A3/B4-08, C3-12
Performance	MB 229.51; Renault RN 0700, RN 0710
Product Sizes	20L, 200L, 1000L and Bulk



SYNPLUS™ 0W/30 ACEA C2

Hi-Tec Synplus™ 0W/30 ACEA C2 is a full synthetic, low to mid SAPS, super high performance engine oil meeting the ACEA C2 (2012) performance level. It combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection whilst promoting fuel efficiency in modern low friction engines in high performance car and light van diesel and gasoline vehicles.

SPECIFICATIONS

Product Code	HII-2129
ACEA	C2-12
Product Sizes	5L, 20L, 200L, 1000L and Bulk

SEMI SYNTHETIC ENGINE OILS



SEMI SYN 10W/40 SN/CF

Hi-Tec Semi Syn 10W/40 SN/CF is a premium quality petrol and small diesel engine oil boosted with synthetic Group III base oils to provide increased engine protection through increased oxidation resistance. Engine cleanliness is promoted by the increased level of dispersants, and the special additives inhibit the formation of sludge.

SPECIFICATIONS

Product Code	HII-2123
API	SN, SM, SL, SJ, SH, CF, CE, CD
Product Sizes	1L, 5L, 20L, 200L, 1000L and Bulk



SEMI SYN 5W/30 SN/GF-5

Hi-Tec Semi Syn 5W/30 SN/GF-5 and 10W/30 SN/ GF-5 are the ideal lubricants for engine protection and fuel efficiency in new as well as older petrol engines. Made with synthetic and Group III base oils and a specially selected additive system, these oils provide higher resistance to oxidation to combat higher internal engine operating temperatures. **Also available in Semi Syn 10W/30 SN/GF-5.**

SPECIFICATIONS

Product Code	HII-2117A (5W/30); HII-2070A (10W/30)
API	SN, SM, SL, SJ, SH
ILSAC	GF-5, GF-4, GF-3
Performance	Energy Conserving III, II
Product Sizes	5L (5W/30 only), 20L, 200L, 1000L and Bulk

MINERAL ENGINE OILS



PREMIER LITE 10W/30 SN/CF

Hi-Tec Premier Lite 10W/30 SN/CF is a premium engine oil suitable for most types of normally aspirated and turbocharged petrol and light diesel engines especially those with small clearances. It is strongly recommended for modern multivalve twin cam engines where a low temperature viscosity is required for cold starts, fuel economy and lower emissions. **Also available in SL/CF grade.**

SPECIFICATIONS

Product Code	HII-2122
API	SN, SM, SL, SJ, SH, CF, CE, CD
Product Sizes	1L, 5L, 6L, 20L, 200L, 1000L and Bulk



PREMIER 15W/40 SN/CF

Hi-Tec Premier 15W/40 SN/CF is a premium engine oil suitable for modern naturally aspirated, turbocharged petrol and light diesel engines. It covers a wide variety of vehicles providing excellent start up viscosity whilst maintaining protection at high temperatures. **Also available in SL/CF grade.**

SPECIFICATIONS

Product Code	HII-2124 (SN); HII-2048 (SL)
API	SN, SM, SL, SJ, SH, CF, CE, CD
Product Sizes	1L & 5L (SN only), 6L (SL only) 20L, 200L, 1000L and Bulk



PREMIER 20W/50 SL/CF

Hi-Tec Premier 20W/50 SL/CF is an engine oil suitable for most types of normally aspirated and turbocharged petrol and light diesel engines. It is an excellent choice where a thicker 20W/50 is required to provide protection at higher temperatures. **Also available in 20W/50 SJ grade (4L size only).**

SPECIFICATIONS

Product Code	HII-2043 (SL); HII-2040 (SJ)
API	SL, SJ, SH, CF, CE, CD
Product Sizes	1L, 4L (SJ only), 5L, 6L, 20L, 200L, 1000L and Bulk



PREMIER 15W/50 SM/CF

Hi-Tec Premier 15W/50 SM/CF exceeds the API SM/CF performance level, and is strongly recommended for all multi-valve and modern engines where a low temperature viscosity is required by the engine manufacturer for cold crank starts, but still providing protection in the engine.

SPECIFICATIONS

Product Code	HII-2096
API	SM, SL, SJ, SH, CF, CE, CD
Product Sizes	5L, 20L, 200L, 1000L and Bulk



SUPER 60 SAE 25W/60

Hi-Tec Super 60 SAE 25W/60 is a very specialised engine oil for naturally aspirated and turbocharged four stroke gasoline passenger car and motorcycle engines. It provides vastly improved protection against engine wear, rust and corrosion, high temperature oxidation deposits and sludge formation as well as against low temperature "black sludge" development. **Also available in Super 70 SAE 25W/70.**

SPECIFICATIONS

Product Code	HII-2023 (60); HII-2030A (70)
API	SG/CD
Performance	Ford M2C.153E (D&C); General Motors GM 6085M, GM 6048M
Product Sizes	5L, 20L, 200L, 1000L and Bulk

HIGH PERFORMANCE ENGINE OILS



SHP 20W/50 CL/CF

Hi-Tec Super High Performance (SHP) SL/CF 20W/50 engine oil is the ultimate in protection and performance. This premium quality engine oil is a complex blend of base oils and chemical additives designed to protect the engine and enhance its performance under extreme operating conditions such as high temperature motorway driving or low temperature stop and go driving.

SPECIFICATIONS

Product Code	HII-2044
API	SL, SJ, SH, CF, CD
Performance	Ford M2C.153E
Product Sizes	5L, 20L and 200L



SHP RACING 50, 60 & 70

Hi-Tec Super High Performance (SHP) Racing Oils are very specialised high performance four stroke racing engine oils, which are specially formulated with enhanced zinc levels to ensure trouble-free lubrication of all high stressed racetrack engines. Recommended where high octane gasolines and their mixtures and other high energy fuels such as methanol and nitromethane are employed. **Available in SHP Racing 50, SHP Racing 60 & SHP Racing 70**

SPECIFICATIONS

Product Code	HII-2055 (50); HII-2056 (60); HII-2054 (70)
API	SN, SM, SL, SJ, SH, CF, CE, CD
Product Sizes	5L, 20L and 200L (50 & 60); 20L and 200L (70)



HTO (PAO) 10W/50 SN/CF

Hi-Tec (PAO) 10W/50 SN/CF is a full synthetic super high performance engine oil which combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection. **Also available 10W/60 SN/CF.**

SPECIFICATIONS

Product Code	H11-2129 (10W/50); H11-2059 (10W/60)
API	SN, SM, SL, SJ, SH, CF, CD, CE
Product Sizes	5L, 20L, 200L and Bulk

TWO STROKE AND FOUR STROKE OILS



HP 2 STROKE OIL

Hi-Tec Performance Two Stroke Oil is designed to be used in high performance top tier, two-stroke motor cycle engines and power tools. It is formulated from a high quality mineral base stock with premium additives to create a modern low ash lubricant.

SPECIFICATIONS

Product Code	H18-2135
API	TC
JASO	FA and FB
Performance	ISO-L-EGB
Product Sizes	200ml, 1L, 4L, 20L and 200L



OUTBOARD OIL TCW-3

Hi-Tec Outboard Oil TCW-3 is the latest of an evolutionary chain of lubricating oils developed to meet the changing needs and increasing performance requirements of water cooled Outboard Engines.

SPECIFICATIONS

Product Code	H18-2131
API	TC
Performance	NMMA TC-W3 Recertified
Product Sizes	1L, 4L, 20L and 200L



PREMIER SAE 30

Hi-Tec Premier SAE 30 is a well proven monograde engine oil for four stroke petrol (lawn mowers) and older normally aspirated diesel engines. It gives improved protection against engine wear, high temperature oxidation deposits to engines of older passenger cars and it is also recommended for veteran and vintage cars where high viscosity, low additive oils are required.

SPECIFICATIONS

Product Code	H11-2020
API	SG/CD
US Military	US Military Specification MIL-L-46152B
Product Sizes	1L, 5L, 20L and 200L



OUTBOARD OIL FC-W 10W/30 & 25W/40

Hi-Tec FC-W Outboard Oils are semi-synthetic 10W/30 and 25W/40 lubricating oils developed to meet the changing needs of and increasing severity of performance required of four stroke outboard engines. Hi-Tec FC-W Outboard Oils meet the performance requirements of the NMMA (National Marine Manufacturers Association) FC-W oil standard.

SPECIFICATIONS

Product Code	H18-2137 (10W/30); H18-2136 (25W/40)
API	NMMA FC-W
Product Sizes	1L, 5L, 10L, 20L, 200L and Bulk

TWO STROKE AND FOUR STROKE OILS



SYN 2T OIL

Hi-Tec Syn 2T Motor Oil is a premium fully synthetic low ash, low smoke two-stroke lubricant formulated with specially developed diester base stock for superior lubricity and performance.

SPECIFICATIONS

Product Code	H18-2134
API	TC
JASO	FA, FB, FC and FD
Performance	ISO-L-EGB, -EGC and -EGD; TISI requirements for detergency & lubricity; Piaggio Hexagon
Use	HUSQVARNA chainsaws; ROTAX snowmobile
Product Sizes	1L, 4L, 20L and 200L

MOTORCYCLE OILS



FAST 4 15W/40 SN/MA

Hi-Tec Fast 4 15W/40 SN MA exceeds the JASO MA specification requirements for use in four stroke motorcycles with wet clutches. This specification ensures that this oil has the correct friction requirements with respect to the Dynamic Friction Index (DFI), the Static Friction Index (SFI) and the Stop Time Index (STI) allowing "wet clutches" in four stroke motor bikes to hold and release at the correct time and speed to allow accurate and predictable gear changes.

Also available **FAST 4 Semi Synthetic 10W/40 SN/MA**

SPECIFICATIONS

Product Code	H11-2048B (15W/40); H11-2082A (10W/40)
API	SM, SN, SL, CF, CD, CE
JASO	MA; SE Valve Train Wear Performance
Performance	Ford M2C153E
Product Sizes	1L, 5L, 20L, 200L and Bulk



FAST 4 20W/50 JASO MA SEMI SYN

Hi-Tec Fast 4 JASO MA 20W/50 Semi Syn SL is a superior four-stroke motorcycle lubricant that has been designed to provide the highest protection for your motorcycle. It is formulated using a combination of synthetic technology oils and the latest generation of additive systems to provide a motorcycle lubricant with the ultimate value and protection level.

SPECIFICATIONS

Product Code	H11-2118
API	SL, SJ, SH
JASO	MA, MA2 (T903:2006)
Product Sizes	1L, 5L, 20L, 200L and Bulk



FAST 2 SEMI SYN 2 STROKE OIL

Hi-Tec Fast 2 Semi Syn Two Stroke Oil is designed to be used in high performance top tier two stroke motorcycle engines, chain saws and power tools. It is formulated from a high quality mineral base stock with detergent additives to create a modern low ash low smoke lubricant.

SPECIFICATIONS

Product Code	H11-2126A
API	TC
JASO	FA, FB, FC and FD
Performance	ISO-L-EGB, -EGC and -EGD; TISI specification
Product Sizes	1L, 5L, 20L, 200L and Bulk



FAST 2 SYN ATF

Hi-Tec Fast 2 Syn ATF is a fully synthetic, super premium multifunctional fluid for motorcycles requiring Dexron® III lubricants. It is also suitable for use in automatic and powershift transmissions and industrial and mobile hydraulic systems. Hi-Tec Fast 2 Syn ATF achieves cleaner transmissions and more reliable operation due to the excellent thermal and oxidative stability.

SPECIFICATIONS

Product Code	H13-2680A
Performance	Dexron® III (H)
Product Sizes	1L, 4L, 20L, 200L and Bulk



FLEETMASTER™ SYNTHETIC CJ-4/SN 10W/40

Hi-Tec Fleetmaster™ Synthetic CJ-4/SN 10W/40 is formulated using synthetic base oils for use in heavy duty diesel engines operating in the harsh Australia conditions. The very high dispersant, anti-wear formulation exceeds the requirements of API CJ-4. This lubricant is specifically designed to meet therequirements of the latest US07 emission standards for engines with exhaust treatment systems especially DPf (diesel particulate filters) and cooled EGR (exhaust gas recirculation) using low sulphur fuels.

SPECIFICATIONS

Product Code	HI2-2264
API	CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4; SN, SM, SL
ACEA	E9-12
EURO	Emission Requirements: I, II, III, IV, V, VI
Performance	CAT ECF-3, ECF-2, ECF-1-A; Cummins CES 20081; Detroit Diesel PGOS 93K218; Deutz DQC III-10 LA; Mack EO-D; Premium Plus; Mercedes Benz MB 228.31; MAN M3575; MTU Type 2.1; Renault RVI RLD-3; Volvo VDS-4; Suitable for Detroit Diesel
Product Sizes	20L, 200L, 1000L and Bulk



FLEETMASTER™ EURO 10W/40

Hi-Tec Fleetmaster™ Euro 10W/40 is a full synthetic high performance diesel engine oil designed to meet the ACEA E6 and Euro VI emission requirements.

SPECIFICATIONS

Product Code	HI2-2229
API	CI-4, CH-4, CG-4, CF-4, CF
ACEA	E7-12, E6-12, E4-12
EURO	Emission Requirements: I, II, III, IV, V, VI
JASO	DH-2
Performance	Volvo VDS-3; Mercedes Benz: Sheet 228.51, 235.27; MTU Type 3.1; CAT ECF-1-a; Deutz DQC IV-10 LA; Scania Low Ash; Renault RXD, RGD, RLD, RLD-2
Product Sizes	20L, 200L, 1000L and Bulk



FLEETMASTER™ 5W/30 ACEA E4

Hi-Tec Fleetmaster™ 5W/30 ACEA E4 is a full synthetic heavy duty diesel engine oil designed specifically to meet the UHPD (Ultra High Performance Diesel) lubricant category for vehicles running under severe operating conditions, such as those requiring significantly extended oil drain intervals.

SPECIFICATIONS

Product Code	HI2-2229
API	CI-4, CH-4, CG-4, CF-4, CF
ACEA	E4-12, E7-12
EURO	Emission Requirements: I, II, III, IV, V, VI
Performance	CAT ECF-2; Iveco 18-1804 FE; MAN M3377, M3277; MTU Type 3; Volvo VDS 3; Deutz DQC IV-10; Mack EO-N Premium Plus; Mack EO-M Plus; Global DHD-1; Mercedes Benz MB 228.5; Renault RXD, RLD-2; Scania LDF
Product Sizes	20L, 200L, 1000L and Bulk

MULTIGRADE DIESEL ENGINE OILS



FLEETMASTER™ 15W/40 CK-4

Hi-Tec Fleetmaster™ 15W/40 CK-4 is a heavy duty diesel oil formulated using the latest synthetic technology base oils for use in severe duty high speed four stroke diesel engines with DPf, cooled EGR and other exhaust treatment systems, both turbo-charged and normally aspirated. It is designed to offer greater durability and protection due to its increased shear stability and reduced oxidative thickening, abrasive wear, bore polishing and piston deposits. Hi-Tec Fleetmaster 15W/40 CK-4 can be used in 2017 model vehicles as well as those requiring Euro VI emission standards.

SPECIFICATIONS

Product Code	HI2-2206
API	CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4
ACEA	E7-16, E9-16
EURO	Emission Requirements: I, II, III, IV, V, VI
Performance	CAT ECF-3, ECF-2, ECF-1-A; Cummins CES 20086; Ford WSS-M2C17-F1; Detroit Diesel DDC93K222; Deutz DQC III-10 LA; JASO DH-2; Mack EOS-4.5; MAN M3275, MAN M3575; Mercedes Benz MB 228.31; MTU 2.1; Renault VI RLD-4; Volvo VDS 4.5
Product Sizes	20L, 200L, 1000L and Bulk



FLEETMASTER™ XTREME 15W/40 CJ-4

Hi-Tec Fleetmaster™ 15W/40 CJ-4 is a premium heavy duty diesel engine oil ideal for multifleet applications covering prime movers, medium and light diesels as well as 2 and 4WD vehicles. Suitable for normally aspirated and turbocharged engines. It sustains the effective performance of advanced exhaust-gas after-treatment systems and protects against catalyst poisoning. Suitable for vehicles fitted with DPF systems.

SPECIFICATIONS

Product Code	HI2-2237
API	CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4; SN, SM, SL
ACEA	E9-12, E7-12
EURO	Emission Requirements: I, II, III, IV, V, VI
JASO	DH-2 Demonstration Program
OEM Approvals	Cummins CES 20081; Volvo VDS-4; Mack EO-O; Premium Plus; Renault RVI RLD-3
Performance	CAT ECF-3, ECF-2, ECF-1-A; Duetz DQC III-10 LA; Detroit Diesel PGOS 93K218; MAN M3575; MB 228.31; MTU Type 2.1
Product Sizes	5L, 10L, 20L, 200L, 1000L and Bulk



FLEETMASTER™ 15W/40 CI-4

Hi-Tec Fleetmaster™ 15W/40 CI-4 is a heavy duty diesel engine oil for use in multifleet diesel applications in normally aspirated and turbocharged engines. It is especially effective at sustaining engine durability where cooled EGR and other exhaust emission componentry is used. It meets the performance requirements of many American and European OEMs and associations.

SPECIFICATIONS

Product Code	HI2-2234
API	CI-4, CH-4, CF, SL, SJ
ACEA	E7-12
EURO	Emission Requirements: I, II, III, IV, V
Performance	CAT ECF-2; EFC-1-A; Cummins CES 20076, 20077, 20078; Detroit Diesel 93K215; Duetz DQC III-10; Global DHD-1; MAN M3275; Mack EO-N, Mack EO-M Plus; MB 228.3; Volvo VDS-3; Renault RVI RLD, RLD-2; MTU Type 2
Product Sizes	5L, 10L, 20L, 200L, 1000L and Bulk



FLEETMASTER™ 15W/40 J-TEC

Hi-Tec Fleetmaster™ 15W/40 J-Tec is a shear stable multigrade diesel engine oil designed specifically to meet the JASO DH-1 performance level for use in modern Japanese diesel engines. It is suitable for both normally aspirated and turbocharged engines.

SPECIFICATIONS

Product Code	HI2-2208
API	CI-4, CH-4, CG-4, CF-4, SL, SJ
ACEA	E7, E5, E3, B4, B3, A3
EURO	Emission Requirements: I, II, III, IV
JASO	DH-1, DHD-1
Performance	CAT ECF-1-A; Cummins 20071, 20072, 20076, 20077, 20078; Mack EO-M Plus; MAN M3275; Volvo VDS3; ZF TE-ML 07C; Renault RVI RLD-2; Mercedes Benz MB228.3, 229.1; MTU Type 2
Product Sizes	5L, 10L, 20L, 200L, 1000L and Bulk



FLEETMASTER™ 10W/40 SEMI SYN

Hi-Tec Fleetmaster Semi Syn CJ-4 10W/40 is formulated using the latest technology mineral and synthetic base oils for use in heavy duty diesel engines operating in the harsh Australia conditions. The very high dispersant, anti-wear formulation exceeds the requirements of API CJ-4. This lubricant is specifically designed to meet the requirements of the latest US07 emission standards for engines with exhaust treatment systems especially DPF (diesel particulate filters) and cooled EGR (exhaust gas recirculation) using low sulphur fuels.

SPECIFICATIONS

Product Code	HI2-2263
API	CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4; SN, SM, SL
ACEA	E9-12
EURO	Emission Requirements: I, II, III, IV, V, VI
Performance	CAT ECF-3, ECF-2, ECF-1-A; Cummins CES 20081; Detroit Diesel PGOS 93K218; Deutz DQC III-10 LA; Mack EO-O; Premium Plus; Mercedes Benz MB 228.31; MAN M3575; MTU Type 2.1; Renault RVI RLD-3; Volvo VDS-4; Suitable for Detroit Diesel
Product Sizes	5L, 10L, 20L, 200L, 1000L and Bulk



MULTITRANS™ ATF

Hi-Tec Multitrans™ ATF is a premium full synthetic automatic transmission fluid with exceptional oxidative resistance, antiwear performance and frictional stability. Providing excellent antirust properties, sludge & varnish control. Specifically designed for use in North American, European and Asian vehicles.

SPECIFICATIONS

Product Code	HI3-2684
JASO	JASO 1-A
Performance	Ford Mercon® V, Allison C-4 and JASO 1-A; GM Dexron® IIIH; Ford Mercon and Ford / BTR 4 speed 85LE and 95LE fluids; AE, Aisin Warner, Audi, BMW, Chrysler, Daimler, Ford Mercon®, GM Dexron® III (H), Honda, Hyundai, Jaguar, JASO, JATCO, JWS, Kia, Mazda, Mercedes Benz, Mitsubishi, Nissan, Rover, Saab, Subaru, Toyota, Volvo, VW and ZF; commercial applications
Product Sizes	1L, 5L, 20L, 60L, 200L, 1000L and Bulk



MULTITRANS™ PLUS ATF (SYN ATF)

Hi-Tec Multitrans™ Plus ATF is a premium full synthetic automatic transmission fluid designed to meet the long drain ZF TE-ML 14C and 20C performance standards, as well as being suitable for use in many North American, European and Asian vehicles.

SPECIFICATIONS

Product Code	HI3-2677
JASO	JASO 1-A
OEM Approvals	ZF TE-ML 04D, 14C, 16M, 20C; Voith 55.6336.XX (G1363)
ZF	ZF TE-ML 14C suitable for use in ZF Ecomat powershift transmissions in buses, ZF-TE ML 20C for ZF EcoLife Transmissions in buses
Performance	Ford Mercon® V; Allison C-4; MAN M339 F, V-1, Z-1, Voith 55.6335.XX (G607) and 55.6336.XX (G1363) and Volvo 97340 and 97341; GM Dexron® IIIH; Ford Mercon® fluids. All other specifications fulfilled by Hi-Tec Multitrans ATF
Product Sizes	20L, 60L and 200L



ATF DX6

Hi-Tec ATF DX VI is a premium full synthetic automatic transmission fluid specially formulated to meet the requirements of the General Motors Dexron® VI specification.

SPECIFICATIONS

Product Code	HI3-2677
Performance	GM Dexron® VI; Ford Mercon® LV; Ford Mercon® SP; Toyota WS
Suitable Use	ATF DX VI is also suitable for many hydraulic systems where ISO 22 or 32 hydraulic fluids or SAE 10W engine oils are recommended
NOTE	Do not use for CVT, DCT or Ford M2C-33F & M2C-33G (Type F & G transmissions)
Product Sizes	5L, 20L, 60L, 200L, 1000L and Bulk



UNIVERSAL CVT

Hi-Tec Universal CVT Transmission Fluid is a premium full synthetic, Continuously Variable Transmission (CVT) fluid, with excellent anti-foaming, anti-shudder, anti-scuffing and shear stability properties, successfully demonstrated in varying types of CVTs with road tests in numerous vehicles. It is suitable for use in many CVT transmissions especially Audi/ VW, Honda, Mini Cooper and Subaru.

SPECIFICATIONS

Product Code	HI8-2676
Performance	Audi/ VW/VW Chain (TL 52180 G 052 180; G 052 516); BMW (8322 0 136 376, 8322 0 429 154, EZL 799A); Daihatsu (CVTF-DC, CVTF DFE); Dodge/Jeep/MOPAR (NS-2, CVTF+4); Ford Chain and Belt (CVT23, CVT30, Mercon C); GM/Saturn (DEX-CVT); Honda (HMMF, HCF-2, CVT-F 05); Hyundai / Kia (SP-CVT 1); Mazda (CVTF, CVT3320); Mercedes Benz (236.20); Mini Cooper (EZL 799A); Mitsubishi Diaqueen (CVTF-J1, CVTF-J4*); Nissan (NS-1, NS-2, NS-3*); Punch (EZL 799A); Shell Green IV; Subaru (NS-2, Lineartronic CVTF, K0425Y0710, CV-30, High Torque CVT Fluid); Suzuki (TC, NS-2, CVTF Green 1, CVTF Green 2*); Toyota/Lexus (TC, FE*) *Low viscosity CVT fluid
Product Sizes	1L, 5L, 20L and 200L



ATF DX3

Hi-Tec ATF DX3 is an automatic transmission fluid for use in older automatic transmissions requiring Dexron® III or Mercon® performance. It is also suitable for use in other transmissions, such as Allison C4 and TES-389, and power steering, pump and hydraulic applications.

SPECIFICATIONS

Product Code	HI3-2688
ZF	ZF TE-ML 05L, 09L, 14A & 21L
Performance	General Motors Dexron® III; Ford Mercon®, XL-12; Allison C-4, TES-389B; Caterpillar TO-2; Power Steering Fluid applications; BTR 95LE, BTR 85LE; Voith H55.6335.xx; Volvo 97325, 97335 & 97340; Auto Trak II; Many hydraulic systems and smaller rotary air compressors.
Note	Do not use for CVT, DCT or Ford M2C-33F & M2C-33G (Type F & G transmissions)
Product Sizes	1L, 5L, 20L, 60L, 200L, 1000L and Bulk



ATF TYPE 95

Hi-Tec Type 95 ATF is the premium Automatic Transmission Fluid for the Ford 4 speed automatic transmissions made by BTR for the 95LE in V8 and the 85LE in 6-cylinder models.

SPECIFICATIONS

Product Code	HI3-2685
Performance	Type A Suffix A (TASA); Caterpillar TO-2; Ford Mercon®; GM Dexron® II; Volvo 97325
Product Sizes	5L, 20L, 60L, 200L, 1000L and Bulk



POWER STEERING FLUID

Hi-Tec Power Steering Fluid is a new generation premium power steering fluid, suitable for most passenger cars and light commercial steering systems.

SPECIFICATIONS

Product Code	HI3-2688C
Performance	<ul style="list-style-type: none"> Effective anti-wear properties help minimise wear and maximise system life. Effective foam control and oxidation provides smooth operation and longevity of fluid.
Product Sizes	500ml

ARE YOU LOOKING FOR THE RIGHT OIL?

Hi-Tec Oils **NEW Lubesearch app** is available to download for your smartphone



Find the right oil for your vehicle
with precision accuracy



www.hi-tecoils.com.au





SYNGEAR™ 75W/90 GL-5

Hi-Tec Syngear™ 75W/90 GL-5 is a full synthetic limited slip gear oil which offers outstanding high temperature and high load performance properties combined with excellent low temperature fluidity and cold flow properties, excellent corrosion protection and superior seal compatibility.

SPECIFICATIONS

Product Code	HI4-2463
API	Automotive: GL-5; MT-1
US Military	MIL-L-2105D, MIL-PRF-2105E
Performance	Mack GO-J; SAE J2360
Product Sizes	1L, 4L, 20L, 60L, 200L, 1000L and Bulk



SYNSHIFT 75W/140 GL-5

Hi-Tec Synshift 75W/140 GL-5 is a full synthetic gear/limited slip differential oil which offers outstanding high temperature and high load carrying performance combined with excellent low temperature fluidity, cold flow properties, excellent corrosion protection and superior seal compatibility.

SPECIFICATIONS

Product Code	HI4-2468
API	Automotive: GL-5; MT-1
US Military	MIL-L-2105D, MIL-PRF-2105E
Performance	Mack GO-J; SAE J2360
Product Sizes	4L, 20L, 60L, 200L, 1000L and Bulk



SYN ROAD RANGER 50

Hi-Tec Synthetic Road Ranger 50 is formulated from premium polyalphaolefin and ester full synthetic base oils for use in Road Ranger gearboxes and automotive and industrial applications, where extreme pressure properties are not required. The extremely high viscosity index and very low pour point provide a tough, highly adhesive film that provides superior protection against wear to gear-teeth and bearings. **Also available Road Ranger 50 G**

SPECIFICATIONS

Product Code	HI4-2518 (50); HI4-2524 (50 G)
API	GL-1 (Road Ranger 50)
Road Ranger 50G Performance	MT-1; Eaton Transmission Division PS-164 (Rev 7)
Product Sizes	20L, 60L, 200L, 1000L and Bulk



SYNGEAR™ M 75W/90 MB 235.20

Hi-Tec Syngear™ 75W/90 MB 235.20 is a full synthetic gear oil with extended long drain performance of up to 500,000 kms. It is particularly suitable for commercial vehicle axles where enhanced load carrying improved fuel economy, and thermal stability is required. Recommended for the lubrication of differentials, final drives, manual transmissions, transfer cases and other gear applications.

SPECIFICATIONS

Product Code	HI4-2476
API	GL-5; MT-1
US Military	MIL-PRF-2105E
ZF	ZF TE-ML 05B, 07A, 08, 12B, 16F, 17B, 19C, 21A, 21B
Performance	Scania STO 1:0; SAE J2360; Arvin Meritor (axles); Mercedes Benz MB 235.0, 235.6, 235.20
Product Sizes	20L, 60L, 200L, 1000L and Bulk



SYNGEAR™ 75W/90 V EXTRA

Hi-Tec Syngear™ 75W/90 V Extra is a synthetic oil based gear lubricant, particularly suitable for synchromesh transmissions and commercial vehicle axles where enhanced load carrying and thermal stability is required. Hi-Tec Syngear 75W/90 V Extra offers outstanding high temperature & high load performance properties. It carries the Volvo 97312 performance level, with long-drain capability of up to 400,000 kms drain in Volvo axles.

SPECIFICATIONS

Product Code	HI4-2478
API	GL-4, GL-5; MT-1
US Military	MIL-PRF-2105E
ZF	ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B
OEM Approval	Volvo Transmission Oil 97312:012
Performance	Mack GO-J; Mercedes Benz MB 235.8, 235.11; Scania STO 1:0; Arvin Meritor 076-N; DAF; IVECO; MAN M341 E-3, Z-2, 342 M-3; Renault
Product Sizes	4L, 20L, 60L, 200L, 1000L and Bulk



GEAR OIL **RX80**

Hi-Tec RX80 Gear Oil is a manual transmission fluid of advanced design especially developed to provide easier gear changes over a wide temperature range. Hi-Tec RX80 Gear Oil is particularly versatile in cold weather. It reduces shift effort at start-up, as well as controlling transmission noise and idle rattle at operating temperatures.

SPECIFICATIONS

Product Code	HI4-2424
API	GL-4
Performance	SAE 80W
Product Sizes	20L, 60L, 200L and Bulk



ROAD RANGER **50**

Hi-Tec Road Ranger SAE 50 is mineral based blended oil for use in Road Ranger gearboxes and for automotive and industrial applications where extreme pressure properties are not required. The high viscosity index and low pour point provide a tough, highly adhesive film to protect gear teeth and bearings against wear.

SPECIFICATIONS

Product Code	HI4-2477
API	GL-2; GL-1
Product Sizes	20L, 60L, 200L, 1000L and Bulk

PREMIUM AUTOMOTIVE GEAR OILS



GEAR OIL **75W/85 GL-4**

Hi-Tec Gear Oil GL-4 75W/85 is an API GL-4 gear lubricant is specially recommended for manual transmissions and transaxles, automotive axles with hypoid gears operating under low to moderate loads, and spiral bevel gears operating at moderate to severe loads.

SPECIFICATIONS

Product Code	HI4-2471
API	GL-4
Product Sizes	4L, 20L, 60L, 200L, 1000L and Bulk



GEAR OIL **75W/90 GL-4 & GL-5**

Hi-Tec Gear Oils 75W/90 GL-4 and GL-5 are API GL-4/ GL-5 gear lubricants specially recommended for synchronised manual transmissions, front wheel drive transaxle gear boxes, automotive hypoid and spiral bevel axles operating at low to moderate loads.

SPECIFICATIONS

Product Code	HI4-2425 (GL4); HI4-2479 (GL5)
API	GL-4, GL-5
ACEA	E2
Suitable Use	Suitable for service fill of GMH, Ford, Daihatsu, Mazda, Mitsubishi, Nissan, Toyota and all other transmissions requiring either an API GL-4 (SAE 75W/90) or API GL-5 (SAE 75W/90) gear lubricant
Product Sizes	20L, 60L, 200L, 1000L and Bulk



GEAR OIL **80W/90 GL-5**

Hi-Tec Gear Oil 80W/90 GL-5 is a superior GL-5 gear oil designed to provide excellent thermal stability, much improved oil seal life and gear surface life, and much improved corrosion protection to yellow metals. Hi-Tec Gear Oil 80W/90 GL-5 is recommended for initial and service fill and top-up of car, truck and tractor manual transmissions, differentials, final drives and transfer and steering

SPECIFICATIONS

Product Code	HI4-2441
API	GL-5
US Military	MIL-L-2105D
Product Sizes	1L, 4L, 20L, 60L, 200L, 1000L and Bulk



LONG LIFE COOLANT **GREEN**

Hi-Tec Long Life Coolant Green is a general purpose ethylene glycol based antifreeze/coolant concentrate incorporating an advanced formula technology with virtually non-depleting organic acid corrosion inhibitors. It is silicate free for improved pump life and contains no environmentally harmful nitrates, borates, phosphates, amines or nitrites. It is recommended for use in aluminium alloy petrol powered automotive engines, and in heavy duty diesel and natural gas mobile and stationary engines.

SPECIFICATIONS

Product Code	HI8-3240
Performance	ASTM D3306, D4656, D4985, D5345, D6210; AS/NZS 2108.1:1997 Type A; Afnor R15-601; BS 6580; JASO M325 LLC; SAE J1034; JIS K2234 LLC; Audi/SEAT/Skoda; BMW N600 69.0; Caterpillar EC-1; Cummins 90 T8-4; DAF Leyland 74001; Daihatsu; Detroit Diesel/Perkins; Ford WSS-M97B44-C; General Motors GM 1899M; Honda; Hyundai; Isuzu; Komatsu; Mack-RVI; MAN M324 (Diesel Engines); Mazda MES 121C; Mercedes-Benz Sheet 325.3; Mitsubishi ES X64216n; Navistar; SAAB; Scania TI 02-98; Subaru; Toyota TS K2601 G; Volkswagen VW TL774D; Volvo
Product Sizes	1L, 5L, 20L, 200L, 1000L and Bulk



LONG LIFE COOLANT **RED**

Hi-Tec Long Life Coolant Red is an ethylene glycol based antifreeze/coolant concentrate with virtually non-depleting organic acid corrosion inhibitors. It is silicate free for improved pump life and contains no environmentally harmful nitrates, borates, phosphates, amines or nitrites. It is recommended for use in aluminium alloy petrol powered automotive engines, and can be used in heavy duty diesel engines.

SPECIFICATIONS

Product Code	HI8-3250
Performance	ASTM D3306, D4656, D4985, D5345, D6210; AS/NZS 2108.1:1997 Type A; Afnor R15-601; BS 6580; JASO M325 LLC; SAE J1034; JIS K2234 LLC; Audi/SEAT/Skoda; BMW N600 69.0; Caterpillar EC-1; Cummins 90 T8-4; DAF Leyland 74001; Daihatsu; Detroit Diesel/Perkins; Ford WSS-M97B44-C; General Motors GM 1899M; Honda; Hyundai; Isuzu; Komatsu; Mack-RVI; MAN M324 (Diesel Engines); Mazda MES 121C; Mercedes-Benz Sheet 325.3; Mitsubishi ES X64216n; Navistar; SAAB; Scania TI 02-98; Subaru; Toyota TS K2601 G; Volkswagen VW TL774D; Volvo
Product Sizes	1L, 5L, 20L, 200L, 1000L and Bulk



RADIATOR **TREATMENT**

Hi-Tec Radiator Treatment is a general purpose automotive cooling system corrosion inhibitor concentrate. It is suitable for passenger cars and light commercial vehicles. It contains a mixture of highly efficient corrosion and rust inhibitors developed for the newest generation of modern vehicles. It provides long-life corrosion protection for aluminium and ferrous alloys.

SPECIFICATIONS

Product Code	HI8-3400
Performance	<p>Lasts 5 Years/ 200,000 km Intervals - Light car; Lasts 6 Years/ 1,000,000 km Intervals - HD diesel</p> <ul style="list-style-type: none"> • Dilution rate is 40-50ml per litre of distilled water • Fully compatible with the rubber hoses and plastics used in engine cooling systems • Exceeds AS/NZ 2108.1:1997 Type B.
Product Sizes	20L and 200L



MAXI COOL **RADIATOR TREATMENT**

Hi-Tec Maxi Cool radiator treatment is a general purpose, automotive cooling system, Anti-Corrosion concentrate. It is suitable for light commercial vehicles and fully compatible with the rubber hoses and plastics used in automotive cooling systems.

SPECIFICATIONS

Product Code	HI8-3402
Performance	<p>Lasts 5 Years/ 200,000 km Intervals - Light car; Lasts 6 Years/ 1,000,000 km Intervals - HD diesel</p> <ul style="list-style-type: none"> • Dilution rate is 500ml per litre of distilled water • Contains no Ethylene Glycol • Exceeds AS/NZ 2108.1:1997 Type B.
Product Sizes	500ml



LONG LIFE PREMIX COOLANT 33%

Hi-Tec Long Life Premix Coolant 33% is a ready to use blend of organic long life corrosion inhibitors, ethylene glycol and distilled water designed to provide superior corrosion and anti-freeze/anti-boil protection for all types of petrol, diesel and gas engines in passenger vehicles and light trucks. **Available in Red and Green**

SPECIFICATIONS

Product Code	H18-3255 (green); H18-3256 (red)
Performance	ASTM D3306, D4656, D4985, D5345, D6210 AS/NZS 2108.1:1997 Type A; Afnor R15-60; S 6580; JASO M325 LLC; SAE J1034; JIS K2234 LLC; Audi/SEAT/Skoda; BMW N600 69.0; Caterpillar EC-1; Cummins 90 T8-4; DAF-Leyland 74001; Daihatsu; Detroit Diesel/Perkins; Ford WSS-M97B44-C; General Motors GM 1899M; Honda; Hyundai; Isuzu; Komatsu; Mack-RV1; MAN M324 (Diesel Engines); Mazda MES 121C; Mercedes-Benz Sheet 325.3; Mitsubishi ES-X64216; Navistar; SAAB; Scania TI 02-98; Subaru; Toyota TS K2601 G; Volkswagen VW TL774D; Volvo
Product Sizes	1L and 5L



RADIATOR FLUSH

Hi-Tec Radiator Flush is formulated to effectively clean vehicle radiator cooling systems. It is both easy to use and will promote cooling system efficiency when used as directed.

SPECIFICATIONS

Product Code	H18-3390
Performance	<ul style="list-style-type: none"> This product is to be used neat. Flush the system with fresh water prior to using this product. Run engine with Hi-Tec Radiator Flush for 15 minutes, drain out the fluid, flush with water then refill with coolant.
Product Sizes	20L and 200L



COMPLETE FILL COOLANT

Hi-Tec Complete Fill Coolant is a general purpose ready to use automotive cooling system corrosion inhibitor. It is suitable for passenger cars and light commercial vehicles. It contains a mixture of highly efficient corrosion and rust inhibitors developed for the newest generation of modern vehicles. Provides long-life corrosion protection for aluminium and ferrous alloys.

SPECIFICATIONS

Product Code	H18-3390
Performance	<ul style="list-style-type: none"> Lasts 5 Years/ 200,000Kms Interval - Light car; Lasts 6 Years/ 1,000,000 Intervals - HD diesel Exceeds AS/NZ 2108.1:1997 Type B Requires no dilution. Contains no ethylene glycol.
Product Sizes	5L



BRAKE FLUID DOT 3 & 4

Hi-Tec Brake Fluid DOT 3 is a yellow premium quality brake fluid that meets and exceeds all the requirements of the DOT 3 specification. It is suitable for use in hydraulic brake and clutch systems.

Hi-Tec Brake Fluid DOT 4 is a premium quality, high boiling point Brake Fluid that meets and exceeds all the requirements of the DOT 4 specification. For help in identification it is dyed blue in colour.

SPECIFICATIONS

Product Code	H18-3130 (3); H18-3140 (4)
Performance	<ul style="list-style-type: none"> Gently swells rubber seals to enhance sealing & prevent system leaks Equilibrium Reflux Boiling Point is greater than 230°C Wet Equilibrium Reflux Boiling Point is 145°C
Product Sizes	500ml, 4L, 20L and 200L

ADBLUE PRODUCT



BLUE AIR

Hi-Tec Blue Air is an aqueous urea solution, designed to be used with the Selective Catalytic Reduction technology (SCR) of heavy-duty diesel vehicles to reduce emissions of oxides of nitrogen (NOx) from the exhaust system.

SPECIFICATIONS

Product Code	H18-3200
Performance	<ul style="list-style-type: none"> For SCR exhaust systems to absorb NOx emissions Blended by certified Ad Blue manufacturer to ISO 22241 and DIN 70070 quality standards. Ideal for Volvo, Scania, DAF, Iveco, Mercedes Benz, AllRig, Alliance
Product Sizes	15L, 200L and 1000L



FLEET WASH

Hi-Tec Fleetwash is a coconut oil based detergent formulation containing inorganic phosphates for the purpose of removing dirt, mud, oil film and road grime from all washable surfaces.

Hi-Tec Fleetwash can be used for all road, commercial and recreational vehicles, engines, and under bodies. It can be used on magnesium and alloy wheels, tyres and rubber inserts.

SPECIFICATIONS

Product Code	HI8-3170
Dilution Rate	Up to 1:10 parts of water - Manual washing and low pressure cleaning; Up to 1:15 parts of water - High pressure cleaning
Performance	<ul style="list-style-type: none"> • Biodegradable cleaning agent • Water soluble and non-flammable • pH in solution of 7.0 - 8.0 • Heavy Duty • Coconut oil based
Product Sizes	5L, 20L, 200L and 1000L



WATER BASED DEGREASER

Hi-Tec Water Based (WB) Degreaser is a biodegradable, alkaline cleaner that can be used in a wide variety of industrial and commercial applications. Hi-Tec Water Based (WB) Degreaser is formulated to provide a powerful emulsifying action to remove dirt, greases and oils from a range of surfaces.

SPECIFICATIONS

Product Code	HI8-3510
Dilution Rate	1:40 for general cleaning; 1:20 for motor bodies and painted surfaces
Performance	<ul style="list-style-type: none"> • Water based • Biodegradable alkaline cleaner • Cost Effective
Product Sizes	5L, 20L, 200L and 1000L



SUPER SCRUBA HAND CLEANER

Hi-Tec Super Scruba Hand Cleaner is a yellow coloured naturally formulated citrus-based waterless hand cleaner containing grit. It removes grease, oil, industrial grime and dirt.

SPECIFICATIONS

Product Code	HI8-3450
Performance	<ul style="list-style-type: none"> • Appearance: Yellow Cream with citrus odour • Biodegradable: Can be disposed to sewerage systems.
Product Sizes	5L, 20L, 200L and 1000L



ULTRA MAGIC

Hi-Tec Ultra Magic is a concentrated multipurpose cleaner with no phosphates added. Hi-Tec Ultra Magic effectively removes dirt, oil and grime from all washable surfaces. It is non-toxic and does not contain solvents or caustic chemicals. It is non-irritating to skin and is completely safe to use on all washable surfaces.

SPECIFICATIONS

Product Code	HI8-3490
Performance	<ul style="list-style-type: none"> • Water soluble • Biodegradable • Non flammable • Neutral pH - no caustics • Non irritant, non toxic
Product Sizes	5L, 20L, 200L and 1000L



ARMOR KOTE

Hi-Tec Armor Kote is a leather and vinyl protector, when applied to vinyl, leather and rubber surfaces it will produce a gloss leaving the surface looking as new. Hi-Tec Armor Kote is safe to use on hard surfaces such as bumpers, cover strips, dash.

SPECIFICATIONS

Product Code	HI8-3030
Performance	<ul style="list-style-type: none"> • Premium leather and vinyl protector • Protects rubber and other hard surfaces • Water Soluble • Non flammable
Product Sizes	400ml, 4L, 20L and 200L



GLASS CLEANER

Hi-Tec Glass Cleaner leaves glass surfaces sparkling. This streak-proof formula removes smoke, grease and grime. Fingerprints, smudges, dust, road film and surface smears can be wiped away. This fast-acting cleaner can be used on any hard surface.

SPECIFICATIONS

Product Code	H18-8225
Performance	<ul style="list-style-type: none"> For glass, mirrored and hard surfaces Streak-free, blue liquid cleaner easily removes grease, dirt and grime from glass, mirrors and hard surfaces
Product Sizes	400ml



WINDOW CLEANER

Hi-Tec Window Cleaner is a non hazardous, light duty, biodegradable, slightly alkaline cleaner that can be used in a wide variety of industrial, commercial and household window cleaning applications. It is safe to use on most hard

SPECIFICATIONS

Product Code	H18-3560
Performance	<ul style="list-style-type: none"> 100% soluble in water Fully Biodegradable Appearance: Clear blue liquid with slight ammonia smell pH: 9.4 - 10.0 Use straight or dilution rates down to 2.5%
Product Sizes	5L, 20L and 1000L



WINDSCREEN ADDITIVE

Hi-Tec Windscreen Additive is a clear blue liquid concentrate for use in automotive washer reservoirs. It is water soluble and non-flammable.

SPECIFICATIONS

Product Code	H18-3560
Performance	<ul style="list-style-type: none"> Water Soluble Non flammable pH 9.7 - 10.0 Use at 2%-10% dilution
Product Sizes	1L chamber, 5L, 20L and 1000L

CLEANING ACCESSORIES



CLEANING RAGS

Hi-Tec cleaning rags can be used for many different services and applications. The product is ideal for wiping and cleaning excess oil and spills in warehouse and workshop.

SPECIFICATIONS

Product Code	H18-3040-0020 (10kg); H18-3040-0020 (20kg)
Performance	Assorted fabric cleaning rags
Product Sizes	10kg and 20kg



SUPER ZORB

Hi-Tec Super Zorb is a lightweight oil absorbent. It can rapidly absorb liquid and retain the liquid against leaching. It does not break down and does not become slippery when wet as do some other absorbent materials. Hi-Tec Super Zorb is made from crushed zeolite rock containing no free crystalline silica.

SPECIFICATIONS

Product Code	H18-3461
Performance	<ul style="list-style-type: none"> Non toxic Environmentally friendly Fast absorption Meets EPA guidelines
Product Sizes	22L



MECHANICS **DEGREASER**

Hi-Tec Mechanics Degreaser is a rapid action solvent based aerosol grease remover specially formulated for motor mechanics, trades people and consumers seeking extra cleaning power. It contains modern surfactants and solvents.

Hi-Tec Mechanics Degreaser can be used for cleaning oil, grease and grime from car, truck and motor cycle engines, mowers, outboard motors and other machinery.

Applications also include cleaning concrete workshop floors, driveways and other surfaces that are heavily contaminated with oil and grease.

SPECIFICATIONS

Product Code	H18-8230
Characteristics	Flammable Aerosol
Product Sizes	400g



BRAKE & PARTS **CLEANER**

Hi-Tec Brake & Parts Cleaner is a solvent based fluid for cleaning brakes, brake discs, drums, calipers, chains, wire ropes, bearings and other metal parts requiring the removal of heavy grease and contaminants.

SPECIFICATIONS

Product Code	H18-8210
Characteristics	Flammable Aerosol
Product Sizes	352g



TYRE **SHINE**

Hi-Tec Tyre Shine has been specially formulated to spray on for a brand new look.

Suitable for tyres, mudflaps, moulds and vinyl trims.

SPECIFICATIONS

Product Code	H18-8252
Characteristics	Flammable Aerosol
Product Sizes	350g



CARBY **CLEANER**

Hi-Tec Carby Cleaner is a rapid action solvent based aerosol cleaner for carburettors and other fuel dispensing apparatus.

It is designed to remove oil, gum, fuel, varnish and carbon deposits from the equipment and to restore the surface to an "as new" appearance.

SPECIFICATIONS

Product Code	H18-8220
Characteristics	Flammable Aerosol
Product Sizes	400g



DE-RUST **LUBRICANT**

Hi-Tec De-Rust Lubricant is multi-functional water displacing fluid, possessing effective rust preventative, fingerprint suppressant, penetrating fluid and lubricant properties.

Hi-Tec De-Rust Lubricant performs many every day type services in the home as well as industry, having rural, transport, automotive and marine applications. It is non-toxic and will not stain.

SPECIFICATIONS

Product Code	H18-8240
Characteristics	Flammable Aerosol
Product Sizes	400g



EVERYDAY **DEGREASER**

Hi-Tec Everyday Degreaser has been specially formulated to simply spray on and hose off in one application. Removes grease from engines, outboard motors, lawn mowers, trucks, trailers, metal parts, tools, work surfaces, walls, driveways - the uses are endless.

SPECIFICATIONS

Product Code	H18-8251
Characteristics	Flammable Aerosol
Product Sizes	400g



HEAVY DUTY **DEGREASER**

Hi-Tec Heavy Duty Degreaser is formulated with petroleum solvents and a detergent emulsifier. The cleaning action of the solvents is enhanced by the presence of aromatic components which improve penetration and solvency. It can be used for cleaning machinery workshop floors and other surfaces heavily contaminated with grease and oil. Apply liberally, work in with a brush and simply hose off.

SPECIFICATIONS

Product Code	H18-3200
Performance	<ul style="list-style-type: none"> Solvent based Flash Point: 40°C Boiling Point: Greater than 150°C Flammable Liquid
Product Sizes	5L, 20L, 200L and 1000L



PARTS WASH **SOLVENT**

Hi-Tec Parts Wash Solvent offers an effective solution for washing or soaking machine parts. Alternatively it can be sprayed onto oily and greasy surfaces. For heavy build up agitate with a brush and allow to penetrate for a few minutes and wash off.

SPECIFICATIONS

Product Code	H18-3350
Performance	<ul style="list-style-type: none"> Solvent based Appearance: Clear liquid Specific Gravity: 0.78 @ 15°C Flash Point: Approximately 42°C Solubility in Water: Insoluble Flammable Liquid
Product Sizes	5L, 20L, 200L and 1000L



BRAKE **CLEANER**

Hi-Tec Brake Cleaner is a solvent based fluid for cleaning brakes, brake discs, drums, calipers, chains, wire ropes, bearings and other metal parts requiring the removal of heavy grease and contaminants.

SPECIFICATIONS

Product Code	H18-3050
Performance	<ul style="list-style-type: none"> Solvent based Appearance: Clear, colourless liquid Specific Gravity: 0.71-0.72 Solubility in Water: Insoluble Flammable Liquid Flash Point -20°C
Product Sizes	5L, 20L, 200L and 1000L



DE-RUST **OIL**

Hi-Tec De-Rust Oil is a multi-functional water displacing fluid, possessing effective rust preventative, fingerprint suppressant, penetrating fluid and lubricant properties. Hi-Tec De-Rust Oil is a very effective rust preventative for short-term indoor applications. It forms a protective film to inhibit rust and corrosion to many items, such as metal components, tools, sporting equipment, locks, hinges, lawn mowers, outboard motors to name a few.

SPECIFICATIONS

Product Code	H18-3110
Performance	<ul style="list-style-type: none"> Flash Point: 36°C Boiling Point: >149°C Non staining Insoluble in water
Product Sizes	400g(Aerosol - 8230), 20L and 200L



TYRE **SHINE**

Hi-Tec Tyre Shine is a silicone based tyre and bumper shine. It leaves surfaces looking glossy and new. Wash tyres and bumpers or any surface that requires treatment. Allow to dry, then simply spray Tyre Shine on to tyres or bumper surfaces. Bumpers may need a wipe with a clean cloth after spraying.

SPECIFICATIONS

Product Code	H18-3480
Performance	<ul style="list-style-type: none"> Flash Point 30-60°C Insoluble in water
Product Sizes	350g(Aerosol - 8252), 20L and 200L



X55 SOLVENT

Hi-Tec X55 Solvent is a wide boiling range, rapidly evaporating, residue free solvent used for processing, cleaning and degreasing in many industries including printing, paints, adhesives and rubber manufacture.

SPECIFICATIONS

Product Code	H18-3570
Performance	<ul style="list-style-type: none"> Density 0.7 kg/Lt Flash Point < -20°C Flammable Liquid
Product Sizes	20L and 200L



KEROSENE

Hi-Tec Kerosene is a petroleum product miscible with many industrial liquids. Kerosene can be used as both a solvent, able to remove other petroleum products, such as chain grease, and also as a lubricant, with less risk of combustion when compared to using petrol. It can also be used as a cooling agent in metal production and treatment (oxygen-free conditions).

SPECIFICATIONS

Product Code	H18-3220
Performance	<ul style="list-style-type: none"> Clear Liquid Density 0.79g/cm³ @ 15°C Flash Point >38°C Hazardous Goods, Flammable Liquid Insoluble in water
Product Sizes	20L and 200L



BUG RID

Hi-Tec Bug Rid is a potent biocide for killing and preventing re-growth of most types of organisms which grow in fuels. Similarly, Hi-Tec bug rid acts as a fuel tank corrosion inhibitor and fuel lubricant improver.

SPECIFICATIONS

Product Code	H18-3570
Performance	<ul style="list-style-type: none"> Character: Hydrocarbon petroleum solvent Appearance: Clear amber liquid Specific Gravity: 0.90kg/Lt Packing: 4 litre, 20 litre & 200 litre steel drum Shelf Life: 24 months if stored in closed drum Flash point > 61°C. Hazardous Goods, Dangerous Goods Immiscible in water
Product Sizes	20L and 200L

FUEL TREATMENT & CLEANERS



DIESEL FUEL TREATMENT

Hi-Tec Diesel Fuel Treatment is a multifunctional diesel fuel maintenance additive. It is specifically designed to give an overall improvement on most aspects of fuel efficiency.

SPECIFICATIONS

Product Code	H18-3120
Performance	<ul style="list-style-type: none"> Appearance: Clear light brown coloured liquid Density, kg/Lt: 0.82 Flash Point > 61°C Hazardous Goods, Non Dangerous Goods
Product Sizes	300ml, 1L, 5L, 20L and 200L



PETROL INJECTOR CLEANER

Hi-Tec Petrol Injector Cleaner is a new gasoline performance additive specifically formulated to control port fuel injector, intake valve and combustion chamber deposits. Hi-Tec Petrol Injector Cleaner is a hazardous, non dangerous good.

SPECIFICATIONS

Product Code	H18-3360
Performance	<ul style="list-style-type: none"> Fuel injection system is cleaned The active ingredient is USEPA certified Improves engine performance and protects against corrosion Flash Point > 61°C Hazardous Goods, Non Dangerous Goods
Product Sizes	300ml, 1L, 5L, 20L and 200L



VXP-2 GREASE

Hi-Tec VXP-2 is a superior, state of the art lithium complex extra heavy duty grease. It is a high temperature, high extreme pressure (EP) grease designed to meet the demands of the most severe and hostile industrial and off highway automotive applications and conditions.

SPECIFICATIONS

Product Code	H17-1006
Performance	<ul style="list-style-type: none"> • NLGI 2 Purple Lithium Complex grease • Maximum protection against high shock loads • Superior rust and corrosion protection • Excellent mechanical stability • High temperature capability • Prime recommendation for rolling element bearings, plain bearings, chassis parts, gears and couplings
Product Sizes	400g, 450g, 2.5kg, 20kg, 55kg and 180kg



LITHPLEX TAC EP-2 GREASE

Hi-Tec Lithplex TAC EP-2 Grease is a superior, multi-purpose grease possessing excellent lubrication characteristics for a wide range of anti-friction and plain bearings, gears and couplings in automotive, marine, agricultural and industrial application.

SPECIFICATIONS

Product Code	H17-1005
Performance	<ul style="list-style-type: none"> • NLGI 2 Blue Lithium Complex grease • Functional Multi-Purpose Grease for low and high temperatures • Water resistant • Adhesive and cohesive • Prime recommendation for wheel bearings, chassis, boat trailer wheel bearings, electric motors, and ball joints
Product Sizes	400g, 450g, 2.5kg, 20kg, 55kg and 180kg



SUPER RED EP-2 GREASE

Hi-Tec Super Red Grease is an NLGI 2 grease possessing superior lubrication characteristics. It is recommended for bearing lubrication under operating service conditions from normal to unusually severe.

SPECIFICATIONS

Product Code	H17-1004
Performance	<ul style="list-style-type: none"> • NLGI 2 Red Lithium grease with enhanced properties • Can be used as a multipurpose grease for both high and low temperature applications (-20 °C to 130°C). • Recommended for chassis, universal joints and wheel bearings particularly those in vehicles fitted with disc brakes
Product Sizes	400g, 500g, 2.5kg, 20kg, 55kg and 180kg



SUPER MOLYTAC EP-2 GREASE

Hi-Tec Super Molytac EP-2 is a superior, multi-purpose, molybdenum disulphide containing grease possessing excellent lubrication characteristics suitable for use in a wide range of anti-friction and plain bearings, ball joints, CV joints, kingpins, and gears and couplings in automotive, marine, agricultural and industrial application.

SPECIFICATIONS

Product Code	H17-1007
Performance	<ul style="list-style-type: none"> • NLGI 2 Grey Lithium Complex grease • Solid Moly particles give superior heavy load and shock load protection • Maintain effective lubrication even when water contamination cannot be avoided • Prime recommendation for plain, ball, roller bearings; and chassis, universal, CV, (and especially) ball joints.
Product Sizes	400g, 2.5kg, 20kg, 55kg and 180kg



TRUCK & FARM GREASE

Hi-Tec Truck and Farm Grease is a red, smooth, tacky grease recommended for use in bearings, chassis parts, gears and couplings in automotive, agricultural, marine and industrial applications.

SPECIFICATIONS

Product Code	H17-1012
Performance	<ul style="list-style-type: none"> • NLGI 2 Red Lithium Complex grease • Caters for unusually high load service conditions • High film strength maintains grease consistency • Recommended for chassis universal joints, and other general lubrication areas in cars, trucks, tractors, trailers etc
Product Sizes	450g, 2.5kg, 20kg, 55kg and 180kg



LITH EP-2, 1, 0, 00, 000 GREASE

Hi-Tec Lith EP Greases possess excellent lubrication characteristics. They are recommended for bearing lubrication under normal or severely loaded service conditions. The NLGI semi fluid grades No. 000, No. 00 and No. 0, are recommended for "self leveling" applications.

SPECIFICATIONS

Product Code	H17-1017 (000); H17-1002 (00); H17-1001 (0); H17-1016 (1); H17-1003 (2)
Performance	<ul style="list-style-type: none"> • Multi-Purpose Lithium greases • Water Resistant • Bearing and ball joint life extended • High shear stability • Oxidation inhibited • Rust and corrosion inhibited
Product Sizes	450g, 2.5kg, 20kg, 55kg and 180kg



SUPER BLUE 3 GREASE

Hi-Tec Super Blue 3 Grease is an NLGI 3 grease possessing superior lubrication characteristics. It is recommended for bearing lubrication from normal to unusually severe load service conditions.

SPECIFICATIONS

Product Code	H17-1014
Performance	<ul style="list-style-type: none"> • NLGI 3 Blue Lithium Complex grease • Manufactured with selected paraffinic and naphthenic base oils combined with rust, oxidation and corrosion inhibitors • Protects against wear on all moving parts and from shock loads in high load service conditions • High shear stability
Product Sizes	450g, 20kg, 55kg and 180kg



PETROLEUM JELLY

Hi-Tec Petroleum Jelly meets the purity requirements of the BP and EP2005, USP28(NF23) and Japanese Pharmacopoeia (XIV) for white soft paraffin and white petrolatum. Expected shelf life is three years provided the material is stored in closed containers and protected from heat, light and moisture.

SPECIFICATIONS

Product Code	H17-1010
Performance	<ul style="list-style-type: none"> • White, smooth gel • Colour: 1.5 Y Maximum • Brookfield Viscosity (DCA022): 6.0 – 12.0 cPs at 10°C • Cone Penetration (TM 1601): 150 – 170 dmm at 25°C • Drop Point, °C: 45 - 60
Product Sizes	500g, 2.5kg and 20kg



RUBBER GREASE

Hi-Tec Rubber Grease is a premium quality clay thickened grease formulated with castor oil to provide outstanding performance in a wide range of automotive and industrial applications where contact with natural and/or synthetic rubber components is required or likely.

SPECIFICATIONS

Product Code	H17-1011
Performance	<ul style="list-style-type: none"> • NLGI 2 Red Clay thickener in castor oil grease • Appearance: Red, smooth, buttery • Base Oil Viscosity @ 40°C, 315 cSt • Normal Temperature Range, °C: -9 to 80 • Drop Point, °C: >288 • Flash Point, °C: 230
Product Sizes	500g, 2.5kg and 20kg

Also available in the Hi-Tec Oils Grease Range

- **FOOD MACHINERY GREASE**
H17-1009
- **NEVERMELT GREASE**
H17-1008
- **CALCIUM SULPHONATE GREASE**
H17-1025
- **HD HAMMER CHISEL PASTE**
H17-1035
- **COPPER COTE GREASE**
H17-1022
- **ULTRALIFE EPM-2 GREASE**
H17-1031
- **COTTON PICKER SPINDLE GREASE** H17-1065
- **LITHIUM BFT 2 GREASE**
H17-1032
- **HP GREASE**
H17-1036

HEAVY DUTY GREASE PUMPING EQUIPMENT

**LEVER ACTION GREASE GUN****Features**

- Adjustments for high pressure or high volume operation.
- Develops grease pressure up to 12,000PSI.
- Rigid outlet with 4 jaw coupler.
- 3 way loading option.

SPECIFICATIONS

Product Code	HI10-UF-LH450
Use	HD grease Gun

PISTOL GRIP GREASE GUN**Features**

- Cast aluminium pump head for durability and long life.
- Develops grease pressure up to 8,000PSI.
- Bleeder valve for purging air pockets.
- C/W flexible outlet.

SPECIFICATIONS

Product Code	HI10-UF-PM450
Use	HD grease Gun

20KG AIR OPERATED GREASE PUMP KIT**Features**

- Adjustments for high pressure or high volume operation.
- Air Operated grease kit.
- Develops grease pressure up to 12,000PSI.
- 58:1 High pressure pump
- 3 way loading option.

SPECIFICATIONS

Product Code	HI10-AE-KP7247PZ
Use	20KG grease pump kit

MANUAL OIL PUMPING EQUIPMENT

20L & 60L GEAR OIL PUMP**Features**

- Standard spring loaded.
- Swivel drum adaptor thread, suits most plastic & tin drums.
- Telescopic tube, easily finds depth of drum.
- Spout holder seal with 'O' ring nozzle, prevents contamination.

SPECIFICATIONS

Product Code	HI10-AP-1336 (20); HI10-AP-1325 (60)
Use	20 litre & 60 litre gear oil manual pump

ROTARY & LEVER OIL PUMP**Features**

- Approx. 3 revolutions P/litre.
- Solid cast iron construction with lever.
- 3pc steel suction pipe
- 2" bung adaptor.
- Suitable for most motor oils & diesel.

SPECIFICATIONS

Product Code	HI10-AP-2220
Use	Manual rotary oil pump

HIGH FLOW ROTARY DRUM PUMP**Features**

- Flow rates up to 100LPM.
- Solid aluminium construction.
- Steel suction pipe & foot strainer.
- 2" bung adaptor.
- Rotary high flow drum pump.
- Fast efficient transfer of diesel, petrol or kerosene.
- Suitable for oils up to SAE30.

SPECIFICATIONS

Product Code	HI10-AP-
Use	Manual rotary oil pump

AIR OPERATED OIL PUMPS

1:1 RATIO OIL PUMP**Features**

- Capable of delivery flow rates of up to 40L/min.
- Ideal for low viscosity transfer of fluids, oils & lubricants.
- Fluid outlet 3/4" BSP(f) Inlet" BSP(f).
- Air outlet 1/4" BSP(f).A

SPECIFICATIONS

Product Code	HI10-OA-32171
Use	Oil pump

3:1 RATIO OIL PUMP**Features**

- For medium size systems which may involve multiple hose reels & metered guns.
- Flow rates up to 14L/min.
- Available in stub or 205L drum pump sizes.
- Fluid outlet 1/2" BSP(f) Air outlet 1/4" BSP (f)

SPECIFICATIONS

Product Code	HI10-OA-20096
Use	Oil pump

3:1 RATIO OIL PUMP**Features**

- For medium size systems which may involve multiple hose reels & metered guns.
- Flow rates up to 14L/min.
- Available in stub or 205L drum pump sizes.
- Fluid outlet 1/2" BSP(f) Air outlet 1/4" BSP (f)

SPECIFICATIONS

Product Code	HI10-OA-21096
Use	Oil pump



NITRO POLO SHIRT

Constructed of 100 percent cotton with embroidered Hi-Tec Oils logo on left chest, printed website on rear. Code H18-B/WH POLO



GOLF UMBRELLA

Code H18-UMBRELLA



TOTE BAG

Code H18-TOTE



NITRO BUTTON SHIRT

Constructed of 100 percent cotton with embroidered Hi-Tec Oils logo on left chest, printed website on rear. Code H18-B/RED BUTTON



HTO BEANIE

Code H18-BEANIE



HTO MUG

Code H18-MUG



CARA PEN

Silver barrel with red rubber retrackable. Code H18-PEN



HTO CAPS

Adjustable black Hi-Tec Oils 25th Anniversary caps. Code H18-CAP



HI-TEC OILS UNISEX JACKET

Weatherproof rain jacket. Embroidered logo on front and logo on rear. Code H18-UNI JACKET



THROW OVER SEAT COVER

Temporary throw over seat cover ideal for mechanic workshops. Code H18-3267



WORKSHOP & CORFLUTE SIGNS

600x900mm pre-printed red corflute or 1000x1000mm alu panel customised workshop signs available on request. H18-3333; CORFLUTE-RED



STUBBY COOLER

Code H18-STUBBY HOLDER



Hi-Tec Oils (Head Office)

5 Tarlington Place, Smithfield NSW 2164

Ph: 1300 796 009 | **(02)** 9616 5700 | **Fax:** (02) 9604 1611

www.hi-tecoils.com.au

Hi-Tec Oils (Victoria)

1/ 41-45 Burns Road
Altona VIC 3018

Ph: (03) 9369 5512
Fax: (03) 9369 5682

Hi-Tec Oils (Queensland)

37 Nealdon Drive
Meadowbrook QLD 4131

Ph: (07) 3200 3492
Fax: (07) 3200 7136

Hi-Tec Oils (South Australia)

6-7/ 3A Newcastle Crescent
Cavan SA 5094

Ph: (08) 8162 5807
Fax: (08) 8359 7849

Hi-Tec Oils (Western Australia)

1/ 46 Baile Road
Canning Vale WA 6155

Ph: (08) 9256 4528
Fax: (08) 9455 2129

Hi-Tec Oils (Northern Territory)

15 Bishop Street
Woolner NT 0820

Ph: (08) 8931 4857
Fax: (08) 8931 4981

Hi-Tec Oils (TAS Distributor)

125 Swanston Street
New Town TAS 7008

Ph: 1300 681 296

Hi-Tec Oils (ACT Distributor)

86 Bayldon Road
Queanbeyan NSW 2620

Ph: (02) 6232 9515
Fax: (02) 6232 9511

Hi-Tec Oils (Newcastle)

1/ 71 Mitchell Road
Cardiff NSW 2285

Ph: (02) 4956 6000
Fax: (02) 4956 6888

Hi-Tec Oils (Port Lincoln)

Pine Freezers Road
Port Lincoln SA 5606

Ph: 0409 162 582
Fax:

Hi-Tec Oils (Auckland)

2 Mahunga Drive
Mangere Bridge NZ 2022

Ph: (09) 951 8101
Fax: (09) 951 8109

Hi-Tec Oils (Christchurch)

16 Moncur Place
Middleton NZ 8024

Ph: (09) 951 8101
Fax: (09) 951 8109

Distributed by:

